



JUMP CONVEYORS

50' / 60' / 80' / 100'

- Flexible conveyors **easily shift in and out** of operation depending on transfer length requirement. ■
- Custom-engineered conveyor truss design **extends conveyor life** in rugged applications. ■
- Adjustable height discharge achieves more accurate **on target feeding** reducing transfer point maintenance. ■
- Tried and true Superior brand components require fewer changeouts, which **lowers operating cost**. ■

SPECIFICATIONS AND OPTIONS

GENERAL SPECS

Tons Per Hour (TPH): Up to 1,200

Belt Widths (inches): Up to 42

Belt Speed (FPM): 400

OPERATING DIMENSIONS	50'	60'	80'	100'
Conveyor Length (m)	50'-0" (15.2)	60'-0" (18.3)	80'-0" (24.4)	100'-0" (30.5)
Conveyor Ground Length (m)	45'-10" (14.0)	55'-5" (16.9)	79'-9" (24.4)	94'-9" (28.9)
Raised Height to Center of Pulley (m)	12'-9" (3.9)	12'-9" (3.9)	10'-1" (3.0)	11'-6" (3.5)
Lowered Height to Center of Pulley (m)	6'-7" (2.0)	6'-11" (2.1)	14'-1" (4.2)	7'-0" (2.4)
TRAVEL DIMENSIONS				
Travel Length - 36" Belt Width (m)	54'-8" (16.7)	64'-8" (19.8)	84'-9" (25.9)	38'-3" (11.7)
Travel Height - 36" Belt Width (m)	9'-0" (2.7)	9'-1" (2.7)	9'-0" (2.7)	13'-10" (4.2)
Travel Width - 36" Belt Width (m)	9'-2" (2.8)	9'-3" (2.8); Dual 10'-1" (3.0)	9'-1" (2.7)	9'-5" (2.8); Dual 10'-5" (3.1)
Weight at Axle - 36" Belt Width (kg)	4,553 (2,065)	4,700 (2,131)	7,000 (3,175)	8,700 (3,946)
Weight at Kingpin - 36" Belt Width (kg)	1,910 (866)	2,400 (1,088)	3,000 (1,360)	2,900 (1,315)



EXTERRA® PRIMARY BELT CLEANER

- EXTERRA® PRIMARY BELT CLEANER
- EXTERRA® SFL DUAL BELT CLEANER
- HIGHWAY PACKAGES
- RADIAL HOPPER
- ADJUSTABLE HEIGHT DISCHARGE



DISCHARGE HOOD

- FIXED HEIGHT SUPPORT
- DISCHARGE HOOD
- LANDING LEGS
- TOWING EYE
- MOXIE® ROLLS



ROAD PORTABLE

- URATHON® RETURN ROLL
- IMPACT IDLERS
- BELT COVERS
- AUTO GREASERS
- BELT SCALE