



STACKABLE CONVEYORS

50' / 60'

- **Greatly reduce freight** when you transport up to eight Stackable Conveyors on one trailer.
- Multipurpose conveyors can be used to **transfer or stockpile** material.
- **Numerous options** to best fit the conveyors into your desired applications.
- Auction statistics confirm Superior Stackable Conveyors have the **highest resale value** in the industry.

FEATURES



STACKABLE PLUS WITH BEND



STACKABLE PLUS WITH UNDERCARRIAGE



TOWING EYE



HEAD SUPPORTS



MODULAR HOPPER W/ STACKABLES



MODULAR HOPPER W/ STACKABLES

- FIFTH WHEEL HITCHES
- HIGHWAY PACKAGES
- 3 CONVEYOR SUPPORT OPTIONS
- PIT OR ROAD PORTABLE AXLES
- 9' HORIZONTAL BEND
- EXTERRA® PRIMARY BELT CLEANER

- MOXIE® ROLLS
- IMPACT LOAD AREA
- RADIAL HOPPER
- PINNING TAB SUPPORT BRACKETS
- URATHON® RETURN ROLL
- TELESCOPING LEGS

- TOW EYE
- ANCHOR PIVOT PLATE

PHOTO GALLERY



SPECIFICATIONS

CONVEYOR	STACKABLE	STACKABLE PLUS
Radial Receiving Hopper	○	○
Exterra® Belt Cleaner	○	○
Backstop	○	○
3-Ply Belt Upgrade	○	○
Vulcanized Splice	○	○
Head and Tail Supports	○	○
Heavier Truss	—	●
Truss Bends for Low Profile Tail	—	○
Undercarriage with Swivel Box	—	○
Tow Eye	—	○
Anchor Pivot Plate	—	○

● STANDARD ○ AVAILABLE — N/A

GENERAL SPECS

Tons Per Hour (TPH): Up to 850 Belt Widths (inches): Up to 48 Incline Angle: 18°

CONVEYOR	50'	60'	50' PLUS	60' PLUS	50' PLUS W/ BEND	60' PLUS W/ BEND
Conveyor Length (m)	50'-0" (15.2)	60'-0" (18.3)	50'-0" (15.2)	60'-0" (18.3)	50'-0" (15.2)	60'-0" (18.3)
Conveyor Ground Length (m)	45'-8" (13.9)	55'-2" (16.8)	49'-2" (15.0)	55'-10" (17.0)	51'-4" (15.6)	61'-5" (18.7)
Raised Height to Center of Pulley (m)	Up to 17'-11" (5.5)	Up to 21'-0" (6.4)	16'-7" (5.0)	19'-8" (6.0)	15'-5" (4.7)	18'-6" (5.6)
Lowered Height to Center of Pulley (m)	12'-5" (3.8)	12'-5" (3.8)	9'-0" (2.7)	7'-11" (2.4)	7'-3" (2.2)	9'-0" (2.7)
Anchor Pivot to Center of Axle (m)	25'-5" (7.8)	31'-2" (9.5)	26'-10" (8.2)	32'-9" (10.0)	28'-2" (8.6)	38'-10" (11.8)

STACKABLE & STACKABLE PLUS CONVEYOR	MAX. STOCKPILE HEIGHT (M)	MAX. STOCKPILE CAPACITY CUBIC YARD (M3)	18° STRAIGHT INCLINE TONS (MT)
50'-0"	18'-6" (5.7)	430 (328)	580 (526)
60'-0"	21'-6" (6.6)	680 (519)	920 (834)

STACKABLE PLUS CONVEYOR W/ BEND	MAX. STOCKPILE HEIGHT (M)	MAX. STOCKPILE CAPACITY CUBIC YARD (M3)	19° INCLINE W/ BEND TONS (MT)
50'-0"	19'-6" (6.0)	490 (374)	660 (598)
60'-0"	22'-6" (6.9)	780 (596)	1100 (997)